

## SH-ADI TENSION PACKER

Model SH-ADI Tension Packer is a retrievable, tension set packer, designed to hold pressure from below. This economical tension packer is for shallow wells where sufficient set-down weight is not available. This packer is primarily used in water flood, oil production or treating applications. They are available for 4" through 9-5/8" casing.

## SPECIAL FEATURES

- Short compact design enables easy running procedures, as well as transport
- Bore through the packer is larger than the drift
- Easy to operate J-Slot control
- Rocker type slips
- Proven one piece packing element
- Multiple release methods
- Parts are interchangeable with other manufacturers



CASING		SETTING RANGE		Size	Tool ID (in.)	Tool OD (in.)	THREAD BOX X PIN					
OD (in.)	Wt (lbs/ft)	Min ID (in.)	Max ID (in.)									
4	9.5-11.6	3.428	3.548	41A	1.937	3.188	2 3/8 EU 8Rd					
4-1/2	12.6-15.1	3.754	3.826	41B		3.609						
	9.5-13.5	3.91	4.09	43A		3.771						
5	15-18	4.25	4.408	43B		4.125						
	11.5-15	4.408	4.56	43C		4.25						
26	1.978				2 3/8 EU 8Rd							
5-1/2		20-23	4.625	4.778		45A2		4.5				
		15.5-20	4.778	4.95		45A4		4.641				
	13-15.5	4.95	5.19	45B	4.781							
5-3/4	22.5				5.191	5.39		45C	5.062			
6	26	5.191	5.39	45D			5.156					
		20-23	5.391	5.56	45E4	5.484						
6-5/8	28-32	5.61	5.791	47A2	2.416	5.656	2 7/8 EU 8Rd					
7	24	5.83	5.937	47A4		5.812						
	38					5.968						
6 5/8	17-20	5.938	6.135	47B2		6.078						
	32-35					6.266						
	26-29					6.453						
7	20-26	6.136	6.276	47C4		6.456		6.578	6.456	6.578	47D2	6.672
	17-20	6.276	6.456	47D4		6.812						
	33.7-39	6.579	6.797	49A2		7.312						
7-5/8	24-29.7	6.798	7.025	49A4		3		7.532	3 1/2 EU 8Rd			
	20-24	7.025	7.125	49B	7.781							
	40-49	7.511	7.725	51A2	8.218							
8-5/8	32-40	7.725	7.921	51A4	4	8.437	4 1/2 EU 8Rd					
	20-28	7.922	8.191	51B		8.593						
	47-53.5	8.3	8.681									
9-5/8	40-47	8.681	8.835									
	29.3-36	8.836	9.063									