

SHIELD-WBP TOP SET

Model WBP is compact, small OD and designed as a high performance drillable bridge plug suitable for almost any temporary or permanent plugging operation. The plug is constructed from select materials which provide a combination of strength and drillability.



SPECIAL FEATURES

- Sets securely in all standard hardness casing
- Ratchet lock rings secure dynamic setting force. Faster and safer run
- One piece packing element and metal back up rings combine for a superior seal
- Can be set directly with Baker wireline setting tools
- Shear studs are Baker style and connect directly to the Adjuster Sub

Please contact sales to inquire about high temperature applications.

CASING		SETTING RANGE		SETTING TOOL	TOOL OD
OD (in.)	Wt T&C (POUNDS)	Min ID (in.)	Max ID (in.)		
2 3/8	4.0-5.8	1.780	2.074	1 11/16" GO	1.75
2 7/8	6.4-6.5	2.340	2.525	1 11/16" GO	2.22
3 1/2	5.7-10.3	2.867	3.258	1 11/16" GO	2.75
3 1/2	12.8-15.8	2.548	2.764	1 11/16" GO	2.43
4	5.6-14	3.340	3.732	#10	3.14
4 1/2	9.5-15.1	3.826	4.090	#10	3.59
5	11.5-20.8	4.154	4.560	#20	3.93
5	11.5-20.8	4.154	4.560	#10	3.93
5 1/2	13-23	4.580	5.044	#20	4.31
5 1/2	13-23	4.580	5.044	#10	4.31
5 3/4	14-25.2	4.890	5.290	#20	4.70
6 5/8	17-32	5.595	6.135	#20	5.37
7	17-35	6.000	6.538	#20	5.68
7 5/8	20-39	6.625	7.125	#20	6.31
8 5/8	24-49	7.310	8.097	#20	7.12
9 5/8	29.3-58.5	8.435	9.063	#20	8.12
10 3/4	32.7-60.7	9.660	10.192	#20	9.43
11 3/4	38-60	10.772	11.150	#20	10.43
11 3/4	60-83	10.192	10.772	#20	9.94
13 3/8	48-84.5	12.175	12.715	#20	11.88
16	65-118	14.576	15.250	#20	14.12
20	94-133	18.730	19.124	#20	18.37