

SXLT RETRIEVABLE PACKER

SXLT Compression-Set Service Packer is designed for high pressure high-temperature service work. The hydraulically operated upper hold-down buttons anchor the packer during high differential pressures from below. The SXLT includes positive rotational locks on all internal connections, allowing transmission of extreme torque through the packer. Backup rings on all O-rings provide reliable sealing at high temperature and pressure. The packer also comes with tool joint connections on extra-long top and bottom subs for hydraulic tong makeup and breakout.

SPECIAL FEATURES

- Heavy-duty mandrel supports high hang-off weights
- Backup rings on O-rings seal for high pressure and temperature
- Tool joint connections are standard
- Rotationally locked end connections for torque transmission
- Quarter-turn set, pickup unset
- Standard automatic jay mechanism

CASING				PACKER				
OD IN	WEIGHT LBS./FT	MIN. I.D IN	MAX ID IN	MAX OD IN	MIN ID IN	THREAD-CONNECTIONS		
4-1/2	15.1-17.7	3.696	3.826	3.593	1.750	2-3/8" I.F.		
	11.6-13.5	3.920	4.000	3.781				
5	15-18	4.276	4.408	4.125				
	11.5-15	4.408	4.560	4.250				
5-1/2	17-23	4.670	4.892	4.500				
	13-17	4.892	5.044	4.641				
7	38-46.4	5.626	5.920	5.525			2.688	3-1/2" I.F.
	32-38	5.920	6.094	5.781				
	26-32	6.094	6.276	5.954				
	17-23	6.366	6.538	6.188				
7-5/8	33.7-39	6.625	6.765	6.453				
	24-29.7	6.875	7.025	6.670				
9-5/8	58.4-59.4	8.407	8.435	8.250	3.750	4-1/2" I.F.		
	43.5-53.5	8.535	8.755	8.365				
	32.3-43.5	8.755	9.001	8.584				
10-3/4	71.1-73.2	9.406	9.450	9.125				
	51-55.5	9.760	9.850	9.500				
11-3/4	60-71	10.586	10.772	10.406				
13-3/8	48-77	12.275	12.715	12.000				

